


PRELIMINARY REV X0 22MAY09

PRELIMINARY REV X1 14JUL09
 REVISE NOTE 5 TO INCLUDE 'MOMENTARY'
 RE-TYPE NOTES.
 ADD LENS DIM. 0.340 OD

PRELIMINARY REV X2 27JUL09
 CORRECT SWITCH TERMINALS
 FROM 4-5-6 TO 1-2-3

NOTES:

1. SWITCH: OMRON MICROSWITCH, D2F-01L, MICRO-VOLTAGE, MICRO-CURRENT.
2. SWITCH ACTUATION FORCE: 9 OZ.
3. TRAVEL: 0.12.
4. WEIGHT: 0.5 GRAMS
5. SWITCH ACTION: MOMENTARY, SNAP ACTION SWITCH.
6. TERMINALS: PCB, SELF-CLINCHING, & SOLDER TYPE.
7. CONTACT CONFIGURATION: SPDT, 1NO & 1NC, GOLD ALLOY.
- 7A. MINIMUM APPLICABLE LOAD: 1mA @ 5VDC
8. SWITCH VOLTAGE: 5-30 VDC.
9. SWITCH CURRENT: 16mA - 100mA
10. RATING: MICRO-LOADS: 0.1 @ 30VDC.
11. INSULATION RESISTANCE: 100M-OHMS MINIMUM (@500 VDC).
12. CONTACT RESISTANCE: 100M-OHMS MAX.
13. LED: T-1-3/4 (5mm) DISCRETE LED, COLOR(S) TO BE DETERMINED.
14. LED VENDOR: DATA DISPLAY PRODUCTS, P/N 200-NW*



| | | | | | | | | |
|--|-----------|------|----------------|--|--------------|--------------|-------------|-------|
| ELECTRO-MECH COMPONENTS INC. SO. EL MONTE, CA * (626) 442-7180 | | | | LIGHTED MOMENTARY SWITCH PUSHBUTTON MICROSWITCH, SPDT | | | | |
| | | | | FSCM: 07150 | SCALE 2:1 | DRAWN CSM | CHK'D | APV'D |
| LT | REVISIONS | DATE | DIM. IN INCHES | TOL. .XX±0.015 .XXX±0.005 | FILE SW44655 | DATE 22MAY09 | PAGE 1 OF 1 | |